U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371

ATTORNEY'S DOCKET NUMBER

104-248P

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

09/380270

INTERNATIONAL APPLICATION NO.	INTERNATIONAL FILING DATE	412 Rec'd PCT/PTO 27 AUG 1999
PCT/SE98/00347	February 26, 1998	February 28, 1997

TITLE OF INVENTION

DATA-CONVERSION METHOD FOR MULTIBEAM LASER WRITER FOR VERY COMPLEX MICROLITHGRAPHIC PATTERNS

APPLICANT(S) FOR DO/EO/US

THUREN, Anders

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.

2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.

3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39 (1).

4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date

5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))

    a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau). Appln. Enclosed WO 98/38597

    b. ☒ has been transmitted by the International Bureau.

    c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).

6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(3)).

7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(2)).

    a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).

    b. ☐ have been transmitted by the International Bureau.

    c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.

    d. ☒ have not been made and will not be made.

8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).

9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).

10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98./International Search Report with cited references

12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.

13. ☒ A FIRST preliminary amendment.
    ☐ A SECOND or SUBSEQUENT preliminary amendment.

14. ☐ A substitute specification.

15. ☐ A change of power of attorney and/or address letter.

16. ☒ Other items or information:
    1.) International Preliminary Examination Report (PCT/IPEA/409)

    2.) Eight (8) Sheet(s) of FOrmal Drawings

U.S. APPLICATION No. (if known, see 37 CFR 1.5)	INTERNATIONAL APPLICATION NO	ATTORNEY'S DOCKET NUMBER
09/380270	PCT/SE98/00347	104-248P

17. ☒ The following fees are submitted:

CALCULATIONS   PTO USE ONLY

BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(5):

Neither international preliminary examination fee (37 CFR 1.482)
nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO
and International Search Report not prepared by the EPO or JPO. $970.00

International preliminary examination fee (37 CFR 1.482) not paid to
USPTO but International Search Report prepared by the EPO or JPO $840.00

International preliminary examination fee (37 CFR 1.482) not paid to USPTO
but international search fee (37 CFR 1.445(a)(2)) paid to USPTO. $760.00

International preliminary examination fee (37 CFR 1.482) paid to USPTO
but all claims did not satisfy provisions of PCT Article 33(1)-(4) $670.00

International preliminary examination fee (37 CFR 1.482) paid to USPTO
and all claims satisfied provisions of PCT Article 33(1)-(4). $96.00

ENTER APPROPRIATE BASIC FEE AMOUNT = $ 970.00

Surcharge of **$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492(e)). $ --------

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total Claims	12 - 20 =	0	X $18.00	$ --------	
Independent Claims	2 - 3 =	0	X $78.00	$ --------	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)		none	+ $260.00	$ --------	
TOTAL OF ABOVE CALCULATIONS =				$ 970.00	

Reduction of ½ for filing by small entity, if applicable. Verified Small Entity statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28). $ --------

SUBTOTAL = $ 970.00

Processing fee of **$130.00** for furnishing the English translation later than ☐20 ☐30
months from the earliest claimed priority date (37 CFR 1.492(f)).   + $ -------

TOTAL NATIONAL FEE = $ 970.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be
accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). **$40.00** per property   + $ --------

TOTAL FEES ENCLOSED = $ 970.00

Amount to be: refunded	$
charged	$

a. ☒ A check in the amount of $ <u>970.00</u> to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account. No. _____ in the amount of $_____ to cover the above fees.
A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any
overpayment to Deposit Account No. <u>02-2448</u>.

**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR
1.137(a) or (b)) must be filed and granted to restore the application to pending status.**

Send all correspondence to:
Birch, Stewart, Kolasch & Birch, LLP
P.O. Box 747
Falls Church, VA 22040-0747
(703)205-8000

SIGNATURE

<u>SLATTERY, JAMES M.</u>
NAME

<u>28,30</u>
REGISTRATION NUMBER

/tmp August 27, 1999

Form PTO-1390 (REV 1-98) page 2 of 2

IN THE U.S. PATENT AND TRADEMARK OFFICE

APPLICANT: Anders THUREN

INT'L. APPLN. NO.: PCT/SE98/00347

SERIAL NO.: New   GROUP:

FILED: August 27, 1999   EXAMINER:

FOR: DATA-CONVERSION METHOD FOR MULTIBEAM LASER WRITER FOR VERY
       COMPLEX MICROLITHOGRAPHIC PATTERNS

PRELIMINARY AMENDMENT

Assistant Commissioner of Patents   August 27, 1999
and Trademarks
BOX PATENT APPLICATION
Washington, D.C. 20231

Sir:

     The following Preliminary Amendments and Remarks are
respectfully submitted in connection with the above-identified
application.

IN THE SPECIFICATION:

     Before line 1, insert --This application is the national
phase under 35 U.S.C. §371 of PCT International Application No.
PCT/SE98/00347 which has an International filing date of
February 26, 1998 which designated the United States of America.--

IN THE CLAIMS:

CLAIM 3: Line 1, delete "or claim 2"

CLAIM 4:   Line 1, change "any one of the preceding claims"
to --claim 1--

CLAIM 5:   Line 1, change "any one of the preceding claims"
to --claim 1--

CLAIM 6:   Line 1, change "any one of the preceding claims"
to --claim 1--

CLAIM 7:   Line 1, change "any one of the preceding claims"
to --claim 1--

CLAIM 8:   Line 1, change "any one of the preceding claims"
to --claim 1--

CLAIM 9:   Line 1, change "any one of the preceding claims"
to --claim 1--

CLAIM 10: Line 1, change "any one of the preceding claims"
to --claim 1--

CLAIM 11: Line 1, change "any one of the preceding claims"
to --claim 1--

CLAIM 12: Line 1, change "any one of the preceding claims" to --claim 1--

CLAIM 13: Line 1, change "any one of the preceding claims" to --claim 1--

R E M A R K S

The specification has been amended to provide a cross-reference to the previously filed International Application.

The amendment(s) to the claim(s) are merely to delete the multiple dependencies and to place the application into better form prior to examination.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to Deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. §1.16 or under 37 C.F.R. §1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH, STEWART, KOLASCH & BIRCH, LLP

By_____

JAMES M. SLATTERY
Reg. No. 28,380
P.O. Box 747
Falls Church, VA 22040-0747

(703) 205-8000
JMS/tnp

3

09/380270

510 Rec'd PCT/PTO 27 AUG 1999

DATACONVERSION METHOD FOR A MULTIBEAM LASER WRITER FOR VERY COMPLEX MICROLITHOGRAPHIC PATTERNS

Field of the invention

The invention relates to microlithography, in particular to the writing of photomasks for computer displays, microelectronic devices, and precision photoetching. It is also applicable to wafers, optical devices and a variety of electronic interconnection structures such as multichip modules. Other applications are possible, such as printing and graphics, as well as laser projection displays.

Background of the invention

The application discloses a method for data conversion at extremely high through-put in a multi-beam laser plotter. The need for such high capacity comes from two sources: the ever-increasing number of features on photomasks, and increasingly sophisticated designs. For both computer displays, consumer TV screens and microelectronic products there is a rapid development towards at the same time larger sizes and smaller elemental cells. The development is most dramatic with semiconductor memories where a photomask could contain a billion elemental geometries or more. Furthermore, the elemental geometries need not be rectangular, but could be of any shape.

The input data file may be in a compacted hierachical format, but during processing the data volume increases immensely (up to 1000-10 000 Gb per mask) and it is impossible to process the data beforehand and store the data until the time of writing. The datapath must therefore have enough processing capacity to convert the data in real time.

Another issue is the necessity of a small address grid. The writing system for semiconductor masks must be capable of writing features specified in units of 10 nm (nanometers) or less. It has been disclosed in European

(nanometers) or less. It has been disclosed in European
Patent EP 0 467 076 by the same inventor that a combina-
tion of time delays and analog power modulation can be
used to achieve an arbitrarily small address grid. The
5   same patent also discloses the use of several beams and
parallel data paths to increase the through-put of the
writing system.

For a writer with two laser beams two parallel data
paths may be feasible, but current multibeam writers may
10   use up to 32 beams and simple multiplication of a single-
beam datapath would be practically impossible.

There is also a strong desire to have unequal num-
bers of processors and beams, in particular a much larger
number of processors than beams. A second need is to make
15   the system easily scaleable, so that writers for differ-
ent applications with different requirements on capacity
can be configured from standard modules and running iden-
tical software.

In United States Patent US 5 533 170 a high-through-
20 .   put multibeam data path based on parallel rasterizers is
disclosed. Each rasterizer, "geometry engine", converts a
frame of the pattern to a pixel map where each pixel has
a greyscale value from 0 to 16. The bitmaps are distrib-
uted to beam boards via a bus system and loaded into a
25   buffer RAM area in each bus board.

The method in US 5 533 170 requires very high proc-
essing power. In particular every pixel has to be filled
with its proper value and transmitted to the beam boards
for writing. This is done by signal processors and custom
30   ASICs. The writing system has a burst pixel rate of 1600
million pixels per second, and extremely high demands are
placed on the internal data paths. Therefore a system
with parallel buses is used and the result is a complex,
costly and inflexible system.

35   The present invention devices a method for data con-
version that can be used on configurations from one

beam/one processor to tens of beams/hundreds of proces-
sors.

Brief summary of the invention

5   In the present invention the data conversion is
divided in two steps: first cutting the geometries in
scan lines and simplifying them, and then finishing the
conversion of the scan lines at the point of demand, i.e.
in a beam processor in the driving electronics for each
10   beam. The idea is to make as much as possible of the con-
version at the latest possible point, i.e. at the beams.
What is needed at an earlier stage is to separate the
data for different beams and distribute them, and to sim-
plify the data enough to make sure that the beam proces-
15   sors can always handle the data flow.
        There are benefits with the invention in three
areas:
- there is nowhere in the system a pixel map that has to
be filled, therefore a lot of processing power is saved
20   - keeping the information to the beam processors in geo-
metrical form instead of as a pixel map gives a smaller
data volume, making the implementation simpler and more
flexible. Practical tests indicate savings of 4 - 20
times depending on the pattern.
25   - the manipulation of the geometrical data without fill-
ing operations is well suited for algorithmic programs
running on a general-purpose processor, while the final
processing in the beam boards is better served with cus-
tom-logic. Using general purpose processors gives great
30   flexibility. It is possible to increase the performance
simply by moving to faster processors as they become
available, and it is easy to modify or refine the
algorithms to follow the needs of the applications. Cus-
tom algorithms for specific applications or new input
35   formats are easily implemented.

Brief description of the drawings

Figure 1a shows how a round shape 101 combined with
a triangular shape 102 are represented by a pixel map 103
with analog intensities (shown as varying shading). The
5   beam 104 is scanning parallel lines 105. The size of the
writing light spot is larger than a pixel, therefore the
result on the plate will be smoothened to a round figure.

Figure 1b shows the same shapes as in Figure 1a, but
where the geometrical shape are cut into segments 106
10 belonging to different scanlines.

Figure 1c shows the same shapes as in Figure 1b, but
where the segments are replaced by a simplified new
segment 107, with only length and width. As in Figure 1a
the size of the spot will make the written figure smooth.

15 Figure 1d shows the segments in Figure 1c converted
to analog values by the beam processor.

Figure 2 shows three beams 201, 202, 203 forming
interlaced scan lines with the spacing 206. The figure
shows that the beams scan three lines and then retrace
20 while the stage is advanced a distance 207 equal to three
times the scan spacing. There are several possible spac-
ings 205 between the beams, here two times the scan spac-
ing 205 is shown.

Figure 3 shows a preferred embodiment of the inven-
25 tion with two beams and two segmentizers.

Figure 4 shows a preferred embodiment with tree
beams and four segmentizers.

Figure 5 shows how data is buffered to allow all
components to run continuously at full capacity in
30 another preferred embodiment with four segementisers and
three beams.

Function of the invention

Figure 3 shows an embodiment with two processors and
35 two beams writing on a workpiece 301 using a demagnifi-
cation and focusing lens 305. The scanning and advance-
ment between the scans, not shown in this figure, can be

done by the stage or the beams or by a combination of the
two. The pattern, shown as a figure 306 in a square
window 307, is described in the input data read from tape
308 or from a network 309. The input can be stored on
5   local mass storage 310, e.g. on a local hard disk, by the
host computer 311. The host computer sends the input data
to the segmentizers 312, 313 after having performed any
necessary format conversions, scalings, expansion of
hierachical structures, etc. It may use mass storage 310
10   for intermediate storage at any time. Furthermore it cuts
the data into fields that are suitable to the length of
the scan lines and to the size of the data buffers in the
data path. Depending on the complexity of the data a
field can be chosen to be a full writing swath or part of
15   a swath.

        The host computer sends the data for each field to
one of the segmentizers 312, 313, typically in the order
they need to be written and to the first available seg-
mentizer. The host computer maintains a table of where
20   the data for each field is and its status.

        The segmentizers cut the data to each scan line and
forms a list of geometrical elements for each scan line
and a list of scan lines 316, 317. Although the function
of the invention does not depend on it, the segmentizer
25   may simplify the geometries in each scan line, remove any
overlapping geometries and form segments that are rect-
angles with length and width and sort both the lists of
segments and the list of scan lines in order of use by
the writing hardware.

30   The list of scan lines are sent to the interlace
resolvers 314, 315 where the scan lines are separated
depending on which beam they will be written by. New
interlaced lists for each beam are assembled. In Figure 3
the list 317 is split into the interlace lists 318 and
35   319 that are sent to beam processor units, e.g. beam
processor boards 320, 321, each with a beam processor 322
and a modulator 323. In the beam processor boards the

simplified geometry in the scan lists is resolved and
converted to amplitude and time modulation of the laser
beams. Since the beams are scanning the workpiece in
parallel the interlaced patterns 324, 325 are reassembled
5   in the exposed pattern.

Since only one field is written at a time only one
interlace resolver can send data to the beam processors
at a time as is shown by the heavy lines from 315 to 320,
321, unless the transfers are buffered so that the pro-
10   cessing in the beam processors is decoupled from the
datainput.

For a simple case with a small number of beams the
distribution can be done by a multiplexor, i.e. a logic
circuit that accepts a single input data stream from the
15   segmentizer/segmentizers and directs data items to
different outputs according to either their position in
their stream or a tag in the data item.

Figure 3 shows the method in schematic form and in a
practical implementation details may vary, e.g. the two
20   modulators can be a single physical device with two
channels, each segmentizer can use one or several
processors etc.

Preferred embodiments

25   A preferred embodiment of the invention is in a
three-beam laser writer for semiconductor reticles, as is
shown in Figure 4. The writer has a distance between the
scan lines of 0.25 μm and a shortest segment length of
0.25 μm. The maximum conversion burst rate in the beam
30   processors is 60 million segments per second and the
system is writing approximately 60 % of the total time.
Accordingly the system writes 3 * 0.25 μm * 0.25 μm * 60%
* 60 million = 6.75 sq.mm/s.

The data distribution network must be dimensioned
35   for the worst possible case, i.e. the entire area filled
with segments of minimum length, or else it is possible
to supply an input data file that causes the system to

malfunction due to data overload. Each beam processor has
a maximum burst rate of 60 million segments per second
and each segment is described by two data bytes. The
three beam processors therefore have a maximum data
5   consumption of 360 Mb/s, corresponding to 180-240 Mb/s
maximum sustained average rate.

The links between the interlace resolvers and the
beam processors are implemented as a cross-switch network
of parallel links. Each link has a transfer rate of 180
10 Mb/s and the shown network can at any time support three
simultaneous transfers. The throughput of the links
between the segmentizers and the beam processors is 3 x
180 mb/s = 540 Mb/s burst rate which is more than ade-
quate for the worst possible pattern including overhead.
15 Alternatively a simpler network can be used supporting
two or only one transfer.

Figure 5 shows how generous buffers allow all compo-
nents to work independent of all others. The heavy lines
show current data transfers. The interlace resolvers
20 (IR1-IR4) have two output buffers, one for storing new
lists being worked on and one for storing the previous
list waiting for transfer to the beam processors. Since
the segmentizers are typically slower than the interlace
resolvers the buffer memory between S and IR need not
25 store any data, it needs only be large enough to allow S
and IR to work in an asynchronous mode.

The beam processor units have FIFO buffers with room
for several fields. Field n (Fn) is being written and is
read from all FIFOs simultaneously, Fn+1 is transferred
30 from IR1, while IR1 is working on Fn+5. IR2 and IR3 are
one and two fields ahead of IR1, respectively, and the
FIFOs of BP2 and BP3 are storing enough data to make the
bottom of all FIFOs synchronized.

S4 and IR4 have just finished Fn+4 and IR4 is trans-
35 ferring the output from the work buffer to transfer
buffer. At the same time the host computer HC is loading
input data for a new field to S4. In actual operation the

scheduling and transfer of data is more irregular than
Figure 5 leads one to believe, since the fields take
different amounts of time to process and the scheduling
is based on demand and availability. The buffer memories
5   in Figure 5 need not be physically separate but may be
different areas in the same physical memory, and they may
be reassigned dynamically. The processors P1 to P8 may
likewise be 8 physical processors, but they may also be
another number and they may be dynamically reassigned
10   between different tasks.

Figure 5 assumes that data needs to be loaded
sequentially to the beam processor buffers. Using random-
access writing instead of FIFOs would allow smaller
buffer areas, but at the expense of more overhead and
15   more complex management by the host computer. In the
preferred embodiment FIFOs are used.

A real pattern will have a data requirement at least
4 times smaller than the maximum data rate or 45 - 67
Mb/s. A typical writing field is part of a swath 200 μm
20   wide and 10 mm long needing an absolute maximum of 32
million segments or 64 Mb data, in practice not more than
8 million segments or 16 Mb data or 5.3 Mb per beam. 72
Mb buffer memory in the beam processor units (24 Mb in
each unit) will then store several fields as shown in
25   Figure 5. An occasional field with too much data will
cause the FIFO buffer to fill up and the pipelining will
be lost for a couple fields, but the system will recover
gracefully. With a larger number of processors than beams
the writing hardware need only wait for data transfers,
30   not for processing since the subsequent fields are
already in the transfer buffers in the IRs.

The size of the fields can be changed dynamically,
so that the field size is made smaller for extremely
dense patterns and larger for less dense patterns.
35   Even in the case where the data to the beam proces-
sors are only rectangular non-overlapping segments, the
conversion from geometrical elements to time and power in

the beam processor uses a set of rules. First the geome-
try is converted to the hardware-supported time and power
resolution. Secondly, the linearity between the power in
the beam and the position of the edge is only approxi-

5   mate. When the beam is only slightly larger than the dis-
tance between two scan lines, the transient function is
s-shaped and on some photo-sensitive materials there is
an additional sag. Therefore it is advantageous to make
an empirical calibration and store the calibration curve

10   as a lookup table. Furthermore, if the geometrical line-
arity of the scan line is not perfect a stored geometri-
cal correction table is useful.

The invention and embodiments satisfy the need for a
real-time data conversion system for a wide range of

15   applications, also the most demanding. In particular
there is no hard limit to the number of processors that
can be used in typical embodiments, since they use cross-
switch network that is more easily extendible than bus
systems. Systems designed according to the invention can

20   also evolve with the rapidly increasing requirements on
capacity. Since it is suitable to be built with standard
processors, standard computer boards and software in
portable high-level language, it can follow the technical
development which has given a tripling of speed every two

25   years in the past.

The terms and expressions which have been employed
in the foregoing specification are used therein as terms
of descritption and not of limitation, and there is no
intention in the use of such terms and expressions of

30   excluding equivalents of the features shown and descibed
or portions thereof, it being recognized that the scope
of the invention is defined and limited only by the
claims which follow.

CLAIMS

1. A method for fast and accurate writing of very complex patterns on a light sensitive surface comprising
5   the steps of:

providing at least two modulated focused laser beams scanning the surface in interlaced parallel scan lines;

providing for each beam a beam processor unit with data conversion logic and means for modulating said laser
10 beam;

providing input data containing the geometries to be written on the plate in an input format, e.g. a list of polygons;

in a first conversion step fracturing the input data
15 into writing fields, e.g. swaths;

in a second conversion step cutting the geometries in the fractured database into scan lines, and generating for each scan line a scan list containing geometries to be written in the scan line, so called segments, and per-
20 forming said second conversion step in at least two par-allel processors, so called segmentizers, operating simultaneously but on different writing fields;

further distributing said scan lists to the beam processor units in accordance with the interlacing of the
25 scan lines; and

in a third conversion step converting in said beam processor units said scan lists of segments to analog power modulation sequences for said laser beams.

2. A method as in claim 1 where in the segments in
30 the scan lists are simplified geometrical representations of those parts of the input geometries that fall in the scan line.

3. A method as in claim 1 or claim 2 where in the segments in a scan lists are non-overlapping.

35 4. A method as in any one of the preceding claims where in the segments in a scan lists are rectangles with a length and a width.

SUBSTITUTE SHEET (RULE 26)

5. A method as in any one of the preceding claims where in the segments in the scan lists are sorted in the order they will be written by the scanning beam.

6. A method as in any one of the preceding claims where in the conversion in the beam processor units uses a set of conversion rules that are empirically calibrated.

7. A method as in any one of the preceding claims where in the conversion in the beam processor units uses at least one table-lookup function.

8. A method as in any one of the preceding claims where in the scan lists are distributed to the beam processor units via a cross-switch network.

9. A method as in any one of the preceding claims where in the scan lists are distributed to the beam processor units via a bus-system.

10. A method as in any one of the preceding claims where in the scan lists are distributed to the any one of the preceding claims beam processor units by a multi-plexer.

11. A method as in any one of the preceding claims where in the data are pipelined through the second and third conversion steps without intermediate non-volatile storage.

12. A method as in any one of the preceding claims where in beam boards has an input buffer with room for the scan lists for at least two writing fields.

13. A method as in any one of the preceding claims where the transfer between the segmentizers and the beam processor unit are doubel buffered, in one output buffer in the segmentizer and in one input buffer in the beam processor unit.

14. An apparatus for fast and accurate writing of very complex patterns on a light sensitive surface com-prising:

at least two modulated focused laser beams scanning the surface in interlaced parallel scan lines;

for each laser beam a beam processor unit with data
conversion logic and means for modulating said laser
beam;

means for accepting input data containing the geome-
5   tries to be written on the plate in an input format, e.g.
a list of polygons

data processing means for in a first conversion step
fracturing the input data into writing fields, e.g.
swaths;

10   parallel data processing means for in a second
conversion step cutting the geometries in the fractured
database into scan lines, and generating for each scan
line a scan list containing geometries to be written in
the scan line, so called segments;

15   data distribution means for distributing said scan
lists to the beam processor units in accordance with the
interlacing of the scan lines; and

data conversion and beam modulation means in the
beam processors units for, in a third conversion step,
20   converting said scan lists of segments to analog power
modulation sequences on said laser beams.

Figure 1a

Figure 1b:

Figure 1c

Figure 1d

Figure 2

Figure 3

Figure 4a

Figure 4b

Figure 5

BIRCH, STEWART, KOLASCH & BIRCH, LLP

104-248P

P.O. Box 747 ·· Falls Church, Virginia 22040-0747
Telephone: (703) 205-8000 • Facsimile: (703) 205-8050

COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT AND DESIGN APPLICATIONS

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated next to my name; that I verily believe that I am the original, first and sole inventor (if only one inventor is named below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Insert Title.

DATA-CONVERSION METHOD FOR A MULTIBEAM LASER WRITER FOR VERY COMPLEX MICRO-LITHOGRAPHIC PATTERNS

Fill in Appropriate Information - For Use Without Specification Attached:

the specification of which is attached hereto. If not attached hereto,

the specification was filed on _____ as

United States Application Number _____;

and amended on _____ (if applicable)(and/or

the specification was filed on February 28, 1998 _____ as PCT

International Application Number PCT/SE98/00347 _____; and was

amended under PCT Article 19 on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I do not know and do not believe the same was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representative or assigns more than twelve months (six months for designs) prior to this application, and that no application for patent or inventor's certificate on this invention has been filed in any country foreign to the United States of America prior to this application by me or my legal representatives or assigns, except as follows.

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Insert Priority Information: (if appropriate)

Prior Foreign Application(s)

Priority Claimed

9700742-1	Sweden	February 28, 1997	☒ Yes	☐ No
(Number)	(Country)	(Month/Day/Year Filed)		
(Number)	(Country)	(Month/Day/Year Filed)	☐ Yes	☐ No
(Number)	(Country)	(Month/Day/Year Filed)	☐ Yes	☐ No
(Number)	(Country)	(Month/Day/Year Filed)	☐ Yes	☐ No

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional applications(s) listed below.

Insert Provisional Application(s). (if any)

(Application Number)	(Filing Date)
(Application Number)	(Filing Date)

All Foreign Applications, if any, for any Patent or Inventor's Certificate Filed More than 12 Months (6 Months for Designs) Prior to the Filing Date of This Application:

Country	Application Number	Date of Filing (Month/Day/Year)

Insert Requested Information (if appropriate)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States and/or PCT application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States and/or PCT application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to the patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

Insert Prior U.S. Application(s): (if any)

(Application Number)	(Filing Date)	(Status - patented, pending, abandoned)
(Application Number)	(Filing Date)	(Status - patented, pending, abandoned)

I hereby appoint the following attorneys to prosecute this application and/or an international application based on this application and to transact all business in the Patent and Trademark Office connected therewith and in connection with the resulting patent based on instructions received from the entity who first sent the application papers to the attorneys identified below, unless the inventor(s) or assignee provides said attorneys with a written notice to the contrary:

Raymond C. Stewart	(Reg. No. 21,066)	Terrell C. Birch	(Reg. No. 19,382)
Joseph A. Kolasch	(Reg. No. 22,463)	James M. Slattery	(Reg. No. 28,380)
Bernard L. Sweeney	(Reg. No. 24,448)	Michael K. Mutter	(Reg. No. 29,680)
Charles Gorenstein	(Reg. No. 29,271)	Gerald M. Murphy, Jr.	(Reg. No. 28,977)
Leonard R. Svensson	(Reg. No. 30,330)	Terry L. Clark	(Reg. No. 32,644)
Andrew D. Meikle	(Reg. No. 32,868)	Marc S. Weiner	(Reg No. 32,181)
Joe McKinney Muncy	Reg. No. 32,334)	C. Joseph Faraci	(Reg. No. 32,350)
Donald J. Daley	(Reg. No. 34,313)	John W. Bailey	(Reg. No. 32,851)
John A. Castellano	(Reg No. 35,094)		

Send Correspondence to: **BIRCH, STEWART, KOLASCH & BIRCH, LLP**
P.O. Box 747 • Falls Church, Virginia 22040-0747
Telephone: (703) 205-8000 • Facsimile: (703) 205-8050

PLEASE NOTE: YOU MUST COMPLETE THE FOLLOWING:

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

GIVEN NAME/FAMILY NAME	INVENTOR'S SIGNATURE		DATE*
Anders Thurén			99.08.25
Residence (City, State & Country)		CITIZENSHIP	
Taby Sweden	SEX	Swedish	
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)			
Torgnyvängen 21, SE-183 72 Täby Sweden			

GIVEN NAME/FAMILY NAME	INVENTOR'S SIGNATURE	DATE*
Residence (City, State & Country)		CITIZENSHIP
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)		

GIVEN NAME/FAMILY NAME	INVENTOR'S SIGNATURE	DATE*
Residence (City, State & Country)		CITIZENSHIP
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)		

GIVEN NAME/FAMILY NAME	INVENTOR'S SIGNATURE	DATE*
Residence (City, State & Country)		CITIZENSHIP
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)		

GIVEN NAME/FAMILY NAME	INVENTOR'S SIGNATURE	DATE*
Residence (City, State & Country)		CITIZENSHIP
POST OFFICE ADDRESS (Complete Street Address including City, State & Country)		

Page 2 of 2
(Revised 11-98)

*DATE OF SIGNATURE